

## FILE SPECIFICATIONS

- Artwork to be supplied in AI, EPS or PDF file format.
- All text to be outlined, all colours to be set as solid-coated PANTONE® colours. If you need assistance, please refer to your sales manager determine your Pantone colour references via our design team.
- No embedded images.

## LOGO FORMATS


Vector file



Image file



## ARTWORK



Design Area + Gap = Repeat length





33% of Original Artwork

## REVERSE DESIGNS

- When printing a reverse design, a fine white gap will appear on repeat due to ink transparency.
- It is also not possible to print a light colour on a dark background.
- Reverse designs available in up to 3 colours.





**CUSTOM PRINTED TAPE GUIDELINES**


**\*\*GUIDELINES\*\***

Min. spacing in between elements: 0.35mm



Your First Choice Online Electrical

Min. line thickness: 0.3mm



Min. font size: 3mm



- \* Various tape width available: 18mm, 24mm, 36mm, 48mm, 72mm, 96mm, 144mm, 288mm.
- \* MOQs: 1 colour print (1 carton), 2, 3 or 4 colour print (2 cartons).
- \* No fades / gradients (solid colours only).

**TERMS & CONDITIONS**

- All orders require written approval of final artwork proof prior to printing. Omni Group will not be held responsible for any misrepresentations of this proof. Please ensure you have carefully checked the final proof supplied before approval.
- Please allow a 10% variance in colour matching.
- Any cancellations after design work has commenced will be subject to a cancellation fee.